


PACKAGING



MIXING



APPLICATION



USES



SUBSTRATES

GLAZED
FLOOR TILES

DO NOT USE ON
WALL TILES

DESCRIPTION

Tile Grip is a liquid specifically designed to reduce the danger of slipping on wet tiles. *It is recommended for use only on hard, thick floor glazes, ie mosaic and ceramic floor tiles.*

PRECAUTION

A sacrificial or inconspicuous test tile **must be** used to check suitability.

USES

Floor areas subject to slipping when the surface is wet ie:

- Home bathroom and kitchen
- Pool surrounds
- Hospitals
- Any tiled surfaces
- Nursing Homes
- Shopping Centres
- Restaurants

SURFACE PREPARATION

Tile Grip requires floor to be thoroughly cleaned prior to application. All waxes and contaminants must be removed. The floor must then be **left wet**.

APPLICATION

Pour a small amount of Tile Grip over area to be treated. Spread the liquid evenly over the floor with a sponge ensuring all areas are completely covered. **Allow the Tile Grip to work for only 10 minutes** and then it must be completely removed by thorough washing with plenty of **clean water**. **Never allow Tile Grip to dry on the surface of the tile as it may affect the tile's appearance.** Do not allow contact with metals as discolouration may occur. Do not mix with other cleaning solutions or acids. **Avoid contact with wall tiles.** It is recommended to wear gloves for application. Tile Grip works by roughening the surface of the glaze. Tile Grip can reduce the effectiveness of the glaze and/or discolour the tile if directions are not strictly adhered to. *A test area **must be done to determine the suitability for its intended use.** If this treatment is not satisfactory, replacement of the tiles with a non-slip tile is the only option.*

COVERAGE (Approximate)

1 litre covers approximately 10-12m² depending on surface type.

PERFORMANCE DATA

Many tile surfaces are slippery when wet (ie have a very low coefficient of friction). Construction Chemicals Tile Grip can increase the coefficient of friction and reduce slip by as much as 70% on slippery floors.

SPECIFICATION

The anti slip treatment for the ceramic floor tiles shall reduce slip by up to 70% and not alter the surface appearance such as Tile Grip manufactured by Construction Chemicals and shall be applied in accordance with the manufacturer's application instructions.

WARNINGS

Highly corrosive

Contact with eyes even for a short period can cause blindness.

Use with adequate ventilation.

SAFETY DIRECTIONS

Avoid contact with eyes – wear goggles.

Avoid contact with skin – wear rubber gloves.

Avoid breathing spray mist or vapour.

FIRST AID

If poisoning occurs, contact a doctor or poisons information centre.

If swallowed, do not induce vomiting. Give a glass of water.

If skin contact occurs, remove contaminated clothing and wash skin.

Immediately apply Calcium Gluconate gel to affected areas.

If in eyes open, flood with water for at least 15 minutes.

Contains 48 g/L Ammonium Hydrogen Fluoride

UN#2817 HAZCHEM 2R

SHELF LIFE

2 years



1 **ADELAIDE** 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052
1 **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
1 **MELBOURNE** 11 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
1 **PERTH** 11 COLLIE RD WELSHPOOL 6106 PH: (08) 9356 9999 FAX: (08) 9356 9955
1 **SYDNEY** 31 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
1 **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
1 **KUALA LUMPUR** LOT 2 JALAN KECABI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING
40000 SHAH ALAM PH: (603) 5122 2522 FAX: (603) 5122 2526