

Antiroot Additive

ANTIROOT ADDITIVE FOR TREMproof 250GC AND TREMproof 60

Key Benefits Summary

- Reduces root penetration of liquid membrane
- Will not damage most plant roots

PRODUCT INFORMATION

CHARACTERISTICS

- Protects construction materials from undesirable root penetration without damaging plants.
- Provides long-term protection.
- Remains effective also under harsh weathering conditions.
- Is heat-resistant and has a very low vapour pressure. The effectiveness of the active ingredient is virtually unaffected by the high temperatures required to process bitumen and welding roofing felts.
- Has good compatibility with most bituminous construction materials.

METHOD OF APPLICATION

Add full contents of bottle into pail and mix thoroughly for 5 minutes with a electric mechanical mixer. Apply TREMproof 250GC or TREMproof 60 in accordance with Tremco's data sheets.

USAGE

While Tremco Antiroot Additive will provide resistance to most root systems, it is always recommended that plants with non invasive root systems be used in planter boxes and general landscape projects.

COLOUR

Amber

PACK SIZE

100ml

PRODUCT CODE

215114

SHELF LIFE

Provided the product is correctly stored and kept in the original sealed package, its shelf life is at least 2 years.

TECHNICAL INFORMATION

CHEMICAL AND PHYSICAL DATA

Active ingredient:	Approx. 99%
Description:	Oily liquid

CHARACTERISTIC DATA

Density (20°C)	Approx. 1.21 g/cm ³
Solidification point	Approx. -12°C
Boiling point	Above 300°C at 1013 hPa (DIN 53171)
Flast point	Approx. 242°C (DIN 22719)
Ignition temperature	Approx. 425°C (DIN 51794)
Solubility (20°C)	Slightly soluble in water, soluble in bitumen, tar pitches and organic solvents such as toluene and xylene

HEALTH & SAFETY PRECAUTIONS

Antiroot Additive is a viscous liquid. Contact of the product with the skin and the inhalation of vapours should be avoided. The precautions generally recommended for handling chemicals should be observed, eg. wearing of protective clothing, protective gloves and safety goggles. If the product comes into contact with the skin, the affected area should be washed immediately with large amounts of soap and plenty of water; splashes in the eye should be rinsed out immediately with plenty of water. If irritation persists, medical attention should be obtained. Contaminated clothing should be changed at once. The Material Safety Data Sheet (MSDS) must be read and understood prior to use.

TECHNICAL SERVICE

TREMCO has a team of qualified Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

TREMCO products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with TREMCO written instructions and (b) in any application recommended by TREMCO, but which is proved to be defective, will be replaced free of charge.

Any information provided by TREMCO in this document in relation to TREMCO's goods or their use is given in good faith and is believed by TREMCO to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. TREMCO makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.