

Description

GRIPSET BRW PF TAPE is a multi-purpose, self-adhesive sealing band designed for flashing and detailing a variety of surfaces. With outstanding adhesion properties of the butyl rubber backing, the Gripset BRW PF Tape is ideal for sealing internal and external surfaces that require protection against moisture ingress, vibration and flexing. The Gripset BRW PF Tape provides an instant seal to the surface it is applied to, avoiding down time for drying or curing associated with traditional liquid sealant alternatives. Ideally suited for waterproofing, roofing and general building applications, the Gripset BRW PF Tape is designed to be finished over with Gripset adhesives, membranes, coatings, mortars, adhesives and renders.

Features & Benefits

- Peel and stick application
- Primer-less application (on dust free, dry and stable surfaces)
- Excellent adhesion over a variety of surfaces
- Easy workability and deformability over substrates
- Excellent thermal stability
- Flexible
- Outstanding adhesion retention at low temperatures
- Instant sealing properties, no drying required
- Rupture and tear resistant
- Solvent free and non-toxic
- Compatible with Gripset liquid membranes and cement based finishes including tile adhesives, renders and texture coatings

Uses

- Bondbreaker system to wall/floor junctions, joint intersections/transitions
- Sealing puddle flanges, penetrations and waterstops
- Detailing over plumbing pipes, PVC, flashings etc.
- Guttering & roofing
- Patching pin holes and pitted areas on metal surfaces
- General maintenance on surfaces to be covered over with surface finishes

Substrates

- Primed or dense concrete
- Galvanised iron, zincalume, copper, aluminium, Colorbond & most metals
- Timber
- Compressed fibre cement sheeting
- Plasterboard
- Masonry
- Glazed surfaces
- Marble, granite and ceramics
- Plastics and polycarbonate

Surface Preparation

- All surfaces are to be clean, sound, smooth, dry and free of any residual moisture, loose material, dirt, dust, oil, grease, wax residues, laitance, curing compounds, release agents, existing coatings, moss, algae, sharp protruding objects and general surface contaminants that may compromise the adhesion of the overlaid membrane system
- Structurally unsound layers and surface contaminants to be mechanically removed by grinding, abrasive blasting or equivalent methods.
- Masonry surfaces to be pointed flush, and all surface defects including voids, holes, pitted sections, heavy undulations and non-structural cracks to be filled and levelled. Refer to Gripset 11Y enhanced repair mortar or the RLA range of repair mortars and levelling compounds for options
- Building surfaces must be fit for purpose, constructed and installed to manufacturer's recommendations and relevant building standards in force at time of application

Priming

- Over non porous and dense surfaces including metals and PVC plastics, priming is generally not required
- Highly porous or surfaces that contain dust or residues must be primed Refer to [GRIPSET GP, E60](#) or [XPRESS H20 PRIMER PLUS](#) for details
- For damp surfaces, or surfaces containing high levels of residual moisture, Gripset E60 must be used

Application

1. Unroll the BRW PF Tape and measure the required length of joints or area to be sealed
2. Cut the tape using scissors or a sharp knife
3. Remove release paper from the butyl rubber side and position the tape in place, ensuring the fabric face is exposed upwards
4. Press into place, and using a spatula, small vinyl roller or similar ensure all air pockets and creases are pushed out and good connection to substrates is achieved
5. For large runs over joint areas, consider gradual removal of release paper as the tape is being unrolled and adhere into position
6. Finishes can be applied immediately after the tape is adhered in place

Shelf life & Storage

- Product is best used within 12 months of purchase; however properties of product will be unchanged if stored correctly
- Best stored at room temperature
- Do not store in direct sunlight
- Not affected by frost, or cold floors

Packaging

- 80mm x 10m rolls
- 150mm x 10m rolls

Precautions

- Cannot be applied over damp surfaces. Damp surfaces must be sealed/primed with Gripset E60 before applying tape
- Not compatible with solvent based materials applied directly over
- Not to be used for sealing joints in negative hydrostatic applications
- Not to be used as an exposed flashing, or exposed joint seal in external applications - must be finished over with a surface covering
- Not to be used over expansion joints
- Do not apply when surface temperature is below 5°C or above 30°C
- For further information about this product contact RLA Technical Department

Technical Data

Colour	Fabric face: white Butyl backing: grey
Thickness	0.8mm
Solids	100%
Specific weight	1.45g/cm ³
Tensile Strength (EN 12311-1)	>100N longitudinal & transverse directions
Elongation at break (EN 12311-1)	70% longitudinal and transverse directions
Peel adhesion (ASTM D1000)	>80N
Loop Tack Test (ASTM D6195)	>70N
Vertical Flow (ISO 7390)	<10mm
Service temperature	-30° C to 80° C

Warranty Statement:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where the product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with relevant Australian Standards.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

Australian Consumer Law:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

Disclaimer:

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

GRIPSET BRW PF TAPE TDS

Issue Date: 01/10/2024

Author: AR



Address : [215 Colchester Road Kilsyth Victoria 3137](#)

Phone: +61 (8) 8124-7300 or 1800 650 435

Email: technicalsupport@rlapolymers.com.au

Website: www.gripset.com