



# Product Data Sheet

## Omniflex

### Product

**Waterproofing Joint Tape**

### Description

A hydrophobic non-woven polypropylene fleece laminated to a grey pressure sensitive butyl adhesive, supplied on a pre-slit extended filmic release liner.

### Roll Size

80mm x 15 Metre

### Application

Designed to create permanent visco-elastic seals on the wall/floor interface and around drainage apertures in walls and floors. Being pressure sensitive there is no curing time for the tape, so liquid waterproofing membrane may be laid immediately onto the non-woven fleece surface. The product is for use in all wet areas such as kitchens, bathroom, showers, external balconies, roof joins etc. The product offers major benefits in that it contains no volatile organic content, is highly resistant to detergents and bleaches and is compatible with all commonly used sealants.

### Technical Details

Tape Thickness	1.0mm
Non-woven polypropylene fibre mass	50 g/M <sup>2</sup>
Resistance to break – Longitudinal	18 N/cm
Perpendicular	13 N/cm
Peel Adhesion	> 4 N/cm
Service Temperature	-30°C to 80°C

### Surface Preparation

Surfaces should be clean, dry, and free from surface contaminants prior to application. Firm pressure should be applied across the entire surface and the use of a pressure roller is recommended. The split liner allows for easy application, and it is recommended that application be carried out between 5°C and 40°C.

Note: The above figures represent average values. Actual figures can vary. The selection and application of a tape is the responsibility of the buyer. Tape should be stored at room temperature and should not be exposed to sunlight. We reserve the right to make changes without notice to our products and specifications.

For all your waterproofing needs

Bathrooms : Showers : Balconies : Rising Damp : Basements : Rooftops : Retaining Walls : Gutters : Parapets: Ponds :  
Water Features : Swimming Pools : Spas : Penetrating Damp : Concrete Repair : Driveways : Underground Car Parks