



Omniflex

Description

Omniflex is a professionally engineered, self-adhesive, non-shrinking, single-sided butyl tape which features a bonded layer of non-woven fabric.

Material & Structure

- Siliconised Release Liner or Plastic Film Liner
- Premium Butyl Rubber Adhesive
- Non-Woven Polypropylene Fleece

Key Features and Applications

- Non-Shrink
- Odourless
- Easy to Install
- Sound-Absorbing
- Environmentally Friendly
- Solvent & Bitumen Free
- Waterproof
- Resistant to Ageing and Weathering

Omniflex is easily applied, offering instant adhesion to most substrates and long-life durability without leaching. Specifically designed for waterproofing in and around wet areas, it serves as an excellent waterproofing and reinforcing tape. Omniflex is compatible with most, waterproofing membranes, tile adhesives and texture coating systems. Omniflex may be used as a watertight, airtight joint seal or as a flashing tape in house cavities.

TECHNICAL DATA

Compound	Butyl Rubber Adhesive
Lamination	Polypropylene Fleece
Density	Approx. 1.5 g/cm ³
Low Temperature Flexibility	No crackle on surface at -40±2°C
Heat Resistance	No flowing, no crack, no deformation at 95°C±5 for 2h
Solids	100%
Application Temperature	+5°C to +40°C (recommended)
Service Temperature	-40°C to +90°C
Standard Thickness	1mm
Width	100mm or 150mm
Length	10m
Colour	Grey
Shelf Life	12 months in original packaging, stored in cool, dry conditions

For all your waterproofing needs

Bathrooms : Showers : Balconies : Rising Damp : Basements : Rooftops : Retaining Walls : Gutters : Parapets : Ponds :
Water Features : Swimming Pools : Spas : Penetrating Damp : Concrete Repair : Driveways : Underground Car Parks