



The Waterstop Shop®
waterproofing supply professionals

Product Data Sheet

8 Park Road
Oakleigh VIC 3166
1300 319 364

info@waterstop.com.au
www.waterstop.com.au

SealProof

SealProof is a moisture curing, industrial grade, high performance sealant based on solvent and isocyanate free, MS polymer technology. Displaying high early strength and flexible properties SealProof is ideally suited for commercial and industrial applications where fast bonding, high movement and vibration absorbing qualities are required. SealProof is suitable for internal and external applications providing outstanding UV resistant and anti-aging characteristics.

Features & Benefits:

- User and environmentally friendly – contains no solvents, isocyanates, acids or halogens
- Permanently elastic
- Highly flexible
- Low emissions
- Good adhesion on both porous and non-porous substrates
- Excellent durability
- Good weathering resistance, colour stability and UV resistance
- Suitable for use on damp surfaces with no bubble formation
- Good extrudability
- Odourless
- Paintable – see notes
- Colourfast – Non staining
- Does not support fungal growth
- Environmentally friendly

Recommended Use:

- General sealing and bonding of construction elements
- Material assembly where a tenacious elastic adhesive is required
- Elastic bonding in vibrating constructions
- Concrete expansion joints
- Masonry control joints
- Sealing where acoustic properties are required
- Perimeter sealing around window and door frames
- Sealing of penetrations in walls or floors
- Sanitary applications

Melbourne's Premier Waterproofing Supplier

2025 Bathrooms : Showers : Balconies : Rising Damp : Basements : Rooftops : Retaining Walls : Gutters : Parapets : Ponds :
Water Features : Swimming Pools : Spas : Penetrating Damp : Concrete Repair : Driveways : Underground Car Parks

Issue Date: 13 October 2025

Substrates:

- Concrete and masonry
- Ceramics, stone, granite, and marble
- Metals including anodized aluminium and steel
- Glass
- Timber
- PVC and rigid plastics

Important: While SealProof maintains excellent adhesion to most common building substrates, preliminary tests are always recommended on substrates where adhesion is critical

Surface Preparation:

All substrates should be clean, sound, dry and free from dirt, dust, wax, oil or grease residues, loose particles and all contaminants that could compromise the adhesion of the sealant.

Masonry/Brick/Concrete:

Any loose particles or laitance should be removed by hand or mechanical means followed by blowing down surfaces with compressed air. Refer to the Waterstop Shop range of cementitious and epoxy mortars/coatings for remedial options to surfaces where required.

Important: New concrete surface/substrates to be cured at least 21 days before application of SealProof.

Metals:

Surfaces must be free of rust, scale or oxide films. Oil and grease residues to be removed with suitable solvent or degreasing solution. (e.g.. MEK, Acetone). Ensure all trace solvent residues are removed prior to the application of SealProof.

Plastics:

SealProof has good adhesion to rigid plastics, polystyrene, PVC, ABS, Polyamide, PMMA, fibreglass-reinforced epoxy and polyester. All releasing agents, processing oils and other protective agents to be removed **Important:** Avoid bonding plastics including PMMA and polycarbonate in stress-loading applications to avoid possible stress cracking and crazing in these substrates. SealProof is not suitable for PE, PP or PTFE.

Priming:

Priming is generally not required for common building substrates. Highly porous substrates should be primed with a Waterstop Shop primer to avoid air entrapment in the uncured sealant caused by rapid temperature rises in the substrate. For immersed applications, surfaces to be primed with a Waterstop Shop primer. Always ensure primer is thoroughly dry prior the application of SealProof.

Application:

- Application temperature is between 5°C to 35°C
- SealProof can be applied by means of a hand or air operated cartridge or sausage gun
- Avoid 3 sided adhesion to movement joints by installing backer rod to joint
- For best performance, the depth of the joint should be half the width for joints greater than 10mm.
- Extrude the SealProof into the joint ensuring that no air is trapped in the joint
- Tool off sealant to ensure full contact to all sides of the joint and the entirety of the joint volume filled
- Tooling will also break any air bubbles within the sealant bead and displace any air pockets within the joint
- Tooling of the joint surface can be done effectively with a spatula to ensure a concave finish
- When masking tape is used for maintaining neat/straight lines, ensure the tape is removed from sides of joint before the sealant starts to skin over or cures
- In conditions of low atmospheric humidity, it is advisable to spray the surface with a fine mist of water to promote early skinning once joint is finished

Expected coverage per 600ml sausage of SealProof

Joint	Approx. Linear Metres
12mm x 12mm	4.1m
15mm x 8mm	5.0m
20mm x 10mm	3.0m
30mm x 15mm	1.5m

Paintability:

SealProof can be painted after fully cured with water based systems. Important: Due to the number of paints and variants available, it is always recommended to conduct field tests to ensure compatibility with the desired coating. Some coatings may crack or craze as a result of environmental cyclical movement.

Packaging:

Available in 600ml Sausages

Storage / Shelf Life:

- Store sealant in original unopened packaging in a dry location
- Product should not be stored below 10oC or above 30oC for prolonged periods
- Shelf life of product is 24 months from date of manufacturing

General Technical Data:

Product Information:

- Appearance: Paste
- Colour: Grey, Black & White
- Tack Free @ +23°C and 50% RH in 10 minutes

Performance Data:

- Sag (GB/T 1377.6): 0mm
- Shore A (ISO 868): 50
- Elongation at break: >550%
- Tensile Strength: >2.8MPa
- Shear Strength: >2.3MPa
- UV Resistance: Good. No appearance change
- Shrinkage (ISO 10563): <1.5%

Joint Width:

- Maximum joint width: 30mm
- Minimum joint width: 5mm

Melbourne's Premier Waterproofing Supplier

2025Bathrooms : Showers : Balconies : Rising Damp : Basements : Rooftops : Retaining Walls : Gutters : Parapets: Ponds :
Water Features : Swimming Pools : Spas : Penetrating Damp : Concrete Repair : Driveways : Underground Car Parks

Issue Date: 13 October 2025

Precautions / Limitations:

- Not suitable for bonding aquariums
- Not suitable for uses with bituminous surfaces/materials
- Do not apply in temperatures below 5°C or above 35°C
- Not suitable as a glazing sealant
- SealProof can be applied to a wide variety of substrates, however due to variations of specific substances such as plastics per the manufacturer, a preliminary compatibility/adhesion test is always recommended
- For best results use opened sausage the same day to avoid sealant curing in the nozzle
- Avoid spilling sealant on surface materials to prevent possible staining by interaction with other components and finishes. (Testing is always recommended first.)
- For specific chemical resistance please contact The Waterstop Shop
- SealProof can be used for adhering of and sealing on natural stone
- Avoid exposure to high levels of chlorine
- Not suitable for swimming pools or hot tubs
- Will not adhere to polypropylene, polyethylene or polycarbonate

Safety & Handling:

- Avoid contact with skin and eyes
- Wear eye protection and suitable gloves and clothing
- The Safety Data Sheet is available upon request

First Aid:

- Skin: Wash off with warm water and soap
- If swallowed give a glass of water
- IF ON SKIN wash skin with soap and water
- If skin irritation occurs, get medical advice/attention
- IF IN EYES Rinse carefully with water for several minutes
- If eye irritation persists, get medical advice/attention
- For advice or if you feel unwell, contact a Poisons Information Centre: Australia ph 131126, New Zealand ph. 0800 764 766 or a doctor at once

SealProof 10 Year Product Guarantee:

The WaterStop Shop guarantees the performance of SealProof when:

- Applied to properly prepared, structurally sound surfaces
- Tiles are installed in accordance with AS3958
- Waterproofing is installed in accordance with AS3740-2021 (internally) or AS4654.2-2012 (externally) in conjunction with:
 - The WaterStop Shop's written application instructions,
 - all relevant requirements of the National Construction Code (NCC)
 - any relevant local building requirements, and
 - good trade practices

The guarantee is for a period of 10 (ten) years from the time of application and only covers the cost of materials and labour of the original installation when the product is proven and acknowledged to be faulty.

Melbourne's Premier Waterproofing Supplier

2025 Bathrooms : Showers : Balconies : Rising Damp : Basements : Rooftops : Retaining Walls : Gutters : Parapets : Ponds :
Water Features : Swimming Pools : Spas : Penetrating Damp : Concrete Repair : Driveways : Underground Car Parks

Issue Date: 13 October 2025